

UNIVERSAL PRIMER™ UNDERLAYMENT PRIMER

PRODUCT DESCRIPTION

Bostik® Universal Primer is designed for use with Durabond 80P™ Latex Modified Self-Leveling Underlayment and all Bostik Self-Leveling Underlayments. It is a high solids latex primer that seals porous substrates and facilitates bond of the underlayment to the subfloor.

PRODUCT USES

Use Universal Primer over concrete, approved plywood substrates; cement backer board, existing ceramic tile, marble, granite, and terrazzo or cut back adhesive residues.

SURFACE PREPARATION

Surface must be clean, dry, free from, loose materials, oil, grease, sealers, curing compounds, waxes and all other surface contaminants that may inhibit proper bond. Mechanically roughen smooth or polished concrete, terrazzo or existing tile or stone by scarifying or shot blasting. A surface profile similar to a light broom finish or a minimum CSP3 as defined by ICRI is recommended.

APPLICATION OVER PLYWOOD

Maximum joist spacing shall be 16" on center. If the existing floor is less than 1" thick, glue and nail 15/32" or 1/2" APA Underlayment Exterior Grade or C-C Plugged Exterior Grade plywood to the floor. Glue and nail using 5D or 6D (1 1/2" or 2") cement coated screw shank nails 6" on center along the panel edges and a maximum of 8" on center each way throughout the panel.

APPLICATION OVER CUTBACK (ASPHALT) ADHESIVE RESIDUE

Remove as much cutback residue as possible with a sharp razor scraper or similar tool. Sweep or vacuum to remove all loose adhesive and dust. Cutback adhesive should be completely removed by shotblasting in *Heavy* or *Extra Heavy* service requirements as defined by TCA guidelines for service requirements. If solid wood flooring will be glued to the cured underlayment, all cutback adhesive must be removed completely by shotblasting prior to installing Universal Primer.

DIRECTIONS FOR USE

Universal Primer may be applied using a brush, roller or broom. Universal Primer may also be diluted 50/50 with water and sprayed. If Universal Primer is diluted, two coats may be required to apply a sufficient amount especially on porous surfaces. Allow the primer to dry (usually 2-4 hours) until it is tack free and transparent. An insufficient amount of Universal Primer may allow "pin-holes" to form in the underlayment.

COVERAGE

400-600 ft²/gallon depending on the roughness of the substrate.

LIMITATIONS

- All surfaces must be primed.
- Do not freeze.
- Do not use over existing vinyl floors or waterproofing membranes, plastic or metal surfaces.
- Do not apply below 50°F or over frozen surfaces.
- For interior use only.
- Do not mix with the underlayment.
- Natural stone such as marble, limestone & travertine may not tolerate deflection in excess of L/720 (1" in 60 ft), refer to the Marble Institute of America Design Manual for details on specific types of stone.
- Cutback adhesive residue should be completely removed by shotblasting in *Heavy* or *Extra Heavy* service requirements as defined by TCA guidelines for service requirements.
- Do not apply over oriented strand board (OSB), particleboard, Masonite, luaun, or similar unstable substrates.
- Do not use where hydrostatic pressure can occur.

PACKAGING

4 x 1 gallon and 5 gallon pails.



BOSTIK FINDLEY

PLANT LOCATIONS

Middleton, MA 01949
800/7-BOSTIK or 800/726-7845

Temecula, CA 92590
Conyers, GA 30207
Twinsburg, OH 44087
Paulsboro, NJ 08066

TECHNICAL SERVICE
800/523-6530

LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or . The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley written specifications, and is free from defects. **BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER MATTER. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, INDIRECT, CONSEQUENTIAL, ECONOMIC, OR OTHER DAMAGES.**



BOSTIK FINDLEY

Boston Street • Middleton, MA 01949 • Customer Service 888/592-8558 • Technical Service 800/523-6530