


[Products](#)
[Technical](#)
[Distributors](#)
[FAQ](#)
[Company](#)
[SITE](#)
[non-flash t](#)

10 Mountainview Rd., Upper Saddle River NJ 07458-1933
 Tel: 1-800-364-1359

Dura Seal is a registered trademark
 Copyright ©1999 Dura Seal
 All rights reserved

[Dura Seal](#) > [Products](#) > [Color & Seal](#) > [Sealers](#) >

**500 Fas
 Drying Se**



DURA SEAL™ 500 Fast Drying Sealer

MSDS Pages

PRODUCT MSDS

 [500 Fast Drying Sealer - Material Safety Data Sheet](#)

Color & Seal

Fillers

Stains

Sealers

- Super Base Sealer

- 500 Fast Drying

- Quick Dry

PRODUCT DESCRIPTION:

Dura Seal®™ 500 Fast Drying Sealer™ is a penetrating sealer designed to seal bare wood before applying **Dura Seal™ Polyurethane, DURA SEAL™ Dura Finish Liquid Floor Wax or Dura Seal™ Paste Wax**. The fast dry time allows for sealing and topcoating wood floors in a single day. Excellent as a sealer on unglazed tile.



Finish & Protect

DIRECTIONS:

Sport Surface System

Floor Preparation:

1. Properly prepare floor according to NOFMA or NWFA specifications. DURA SEAL™ 500 Fast Drying Sealer should only be applied over bare wood or itself. Any finish already on the floor must be completely removed.

Maintain & Beautify

Warranty



Application on Wood Floors:

1. Apply DURA SEAL™ 500 Fast Drying Sealer with a lambs wool applicator or brush at a coverage rate of 600 square feet per gallon.
2. Allow to dry 2 hours or until dry to the touch.

NOTE: Drying time will be increased by high humidity, low temperature, lack of air movement or applying too heavily.

3. Buff with #2 steel wool and remove all excess material.
4. Apply a DURA SEAL™ finish coat of your choice.

Application on Unglazed Terra Cotta Tile:

1. Apply first coat of DURA SEAL™ 500 Fast Drying Sealer with a lambs wool applicator at a coverage rate of 300 square feet per gallon.
2. Allow to dry at least 6 hours.

NOTE: Drying time will be increased by high humidity, low temperature, lack of air movement or applying too heavily.

3. Apply a second coat of DURA SEAL™ 500 Fast Drying Sealer in the same manner as the first repeating steps 1 and 2 above.
4. Buff with a medium stiff scrubbing brush under buffing machine. Remove all excess material.

5. Apply **DURA SEAL™ Dura Finish Liquid Floor Wax or DURA SEAL™ Paste Wax** according to label directions.

PRODUCT PROPERTIES:

Quality
 Products
 You Can
 Rely On

DRY TIME	Wood Surfaces - Approximately 2 hours. Unglazed Tile Surfaces - Approximately 6 hours.
COVERAGE	Wood Surfaces - Approximately 600 square feet per gallon. Unglazed Tile Surfaces - Approximately 300 square feet per gallon.
CLEAN UP	Clean equipment with paint thinner, turpentine or mineral spirits.
SOLVENT	Non-photochemically reactive.

CAUTION:

COMBUSTIBLE MIXTURE N.Y.F.D. C. OF A. NO.1187

KEEP OUT OF REACH OF CHILDREN.**DANGER:**

Contains mineral spirits. Harmful or fatal if swallowed. Do not take internally. Skin irritant. Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling. Avoid inhalation and use only with adequate ventilation. If adequate ventilation cannot be maintained, wear respiratory protection [NIOSH/MSHA TC23C or equivalent] or leave the area. Do not use or store near heat, sparks, flame or other sources of ignition. Close container after each use.

FIRST AID:

If swallowed, do NOT induce vomiting. CALL PHYSICIAN IMMEDIATELY. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. If affected by inhalation, remove to fresh air. If symptoms persist, CALL PHYSICIAN. In case of eye contact, immediately flush eyes thoroughly with water, then remove any contact lenses. Continue to flush eyes with water for at least 15 minutes. If irritation persists, CONTACT A PHYSICIAN.

ize	SKU #	Case/Pack
GAL	81500	4

1/22/99
lit# DS990008

Copyright 2004. The Sherwin-Williams Company. All rights reserved
Privacy | Privacy(French Version) | Terms of Use