



- Products
- Technical
- Distributors
- FAQ
- Company

SITE
non-flash t

10 Mountainview Rd., Upper Saddle River NJ 07458-1933
Tel: 1-800-364-1359

Dura Seal is a registered tr
Copyright ©1999 Dura
All rights reserved

[Dura Seal](#) > [Products](#) > [Color & Seal](#) > [Stains](#) >

**Fast Dry
Wood Sta**



DURA SEAL™ Fast Dry Wood Stain

MSDS Pages

PRODUCT MSDS

Color & Seal

Fillers

Stains

- Penetrating Finish
- Fast Dry Wood Stain
- Pastels Stain Sealers



[Fast Dry Wood Stain - Material Safety Data Sheet](#)

Finish & Protect

PRODUCT DESCRIPTION:

A wood stain designed to dry in three hours. Dura Seal™ Fast Dry Wood Stain will color the densest wood floor in a single coat. Available in four rich wood tones. Finish with any Dura Seal™ **finishing product**.

Sport Surface System

DIRECTIONS:

PREPARATION:

NEW FLOORS:

1. Properly prepare wood surface according to NOFMA or NWFA specifications.
2. Use a No.100 screen for final screening.
3. Remove all dust with broom or vacuum and tack surface with a clean cloth moistened with mineral spirits.

Maintain & Beautify

OLD FLOORS:

Remove old finish completely and prepare as under New Floors.

Warranty



APPLICATION:

1. The temperature of the wood surface to be stained and the DuraSeal™ Fast Dry Wood Stain, itself, should be approximately 70°F.
2. Stir DuraSeal™ Fast Dry Wood Stain thoroughly before and occasionally during use. Apply a small test sample before proceeding with the entire job to ensure desired color.
3. Apply one coat of DuraSeal™ Fast Dry Wood Stain with a brush, lambs wool applicator or cloth at a coverage rate of 500 square feet per gallon.
4. Remove all excess stain with clean rags within 5-10 minutes. Work in areas small enough to ensure removal of stain within the 10 minutes.
5. Allow stain to dry 3 hours before applying a protective DuraSeal **finish** coat of your choice.



DRYING TIME:

Approximately 3 hours. NOTE: Drying time will be increased by high humidity, low temperature, lack of air movement or inadequate removal of excess stain.

PRODUCT PROPERTIES:

COATS REQUIRED	Apply only one (1) coat
-------------------	-------------------------

DRY TIME	3 Hours
COVERAGE	Approx. 500 sq. ft. per gal.
CLEAN UP	Clean equipment with paint thinner, turpentine or mineral spirits
STORAGE	Store at room temperature. Keep container tightly closed

PHYSICAL PROPERTIES:

RESIN TYPE	Alkyd/Urethane
DENSITY (LBS/GAL)	6.75 - 7.0
% SOLIDS	16 -22
VISCOSITY - CPS	less than 50 cps
VOC (g/l)	673 grams/litre or 5.6 lbs/gal
FLASH POINT	105°F - Seta Flash

HEALTH/SAFETY:

HMIS RATING:	
Health	2
Flammability	2
Reactivity	0

CAUTION:

COMBUSTIBLE MIXTURE N.Y.F.D.C. OF A. NO.1187

KEEP OUT OF THE REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

DANGER:

Contains Petroleum Distillates. Harmful or fatal if swallowed. Do not take internally. Avoid inhalation and use only with adequate ventilation. If adequate ventilation cannot be maintained, wear respiratory protection (NOSH/MSHA TC23C or equivalent) or leave the area. Skin irritant. Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling. Do not use or store near heat, sparks flame or other sources of ignition. Close container after each use.

FIRST AID:

If swallowed, do NOT induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush eyes thoroughly with water, then remove any contact lenses. Continue to flush eyes with water for at least 15 minutes. If irritation persists, get medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical

attention. If affected by inhalation, immediately remove to fresh air. If symptoms persist, CALL PHYSICIAN.

Color	Size	SKU #	Case/Pack
216 ANTIQUE BROWN	GAL	81616	4
221 GOLDEN BROWN	GAL	81621	4
228 MEDIUM BROWN	GAL	81628	4
237 SPICE BROWN	GAL	81637	4

03/30/00
lit # DS990028

Copyright 2004. The Sherwin-Williams Company. All rights reserved
[Privacy](#) | [Privacy\(French Version\)](#) | [Terms of Use](#)